

特殊订货号 Special Design/Option Code

异电压频率: E-Voltage/Frequency	L2B	220VD /380VY 60Hz
L1C 415VY 50Hz	L2D	380VD /660VY 60Hz
L1D 415VD 50Hz	L2E	460VY 60Hz
L1U 400VD 50Hz	L2F	460VD 60Hz

绕组保护 Winding protection		适用的机座号范围 Application Scope
A11	Motor protection with PTC thermistors with three embedded temperature sensors for tripping 绕组带一组三芯串联的 PTC 热敏电阻用于跳闸	All
A12	Motor protection with PTC thermistors with six embedded temperature sensors for alarm and tripping 绕组带两组三芯串联的 PTC 热敏电阻用于报警和跳闸	All
A60	Installation of 3 PT100 resistance thermometers 绕组带三个 PT100 测温元件	100 至 355
A61	Installation of 6 PT100 resistance thermometers 绕组带六个 PT100 测温元件	180 至 355
A72	Installation of 2PT100 screw-in resistance thermometers for rolling-contact bearings 轴承装两个 PT100 测温元件	180 至 355
K45	Anti-condensation heater for 220V 绕组带 220V 防潮加热带	All
机械设计 Mechanical design		
K09*	Terminal box on RHS (View on drive end) 接线盒在右侧 (从驱动端看)	All
K10*	Terminal box on LHS (View on drive end) 接线盒在左侧 (从驱动端看)	All
K11*	Terminal box on top 顶出线 (从驱动端看出线口朝右)	All
K83	Rotation of terminal box by 90°, inserted from drive end 接线盒旋转 90 度, 进线方向为驱动端方向	All
K84	Rotation of terminal box by 90°, inserted from non-drive end 接线盒旋转 90 度, 进线方向为非驱动端方向	All
K85	Rotation of terminal box by 180° 接线盒旋转 180 度	All
K16	Second standard shaft-extension 标准双轴伸	All
W01 (原L05)	SKF bearings SKF 轴承	All
W02 (原L06)	NSK bearings NSK 轴承	All
油漆 Paint finish		
K24	Unpainted, only primed 不喷面漆, 只涂底漆	All
Y53	Standard finish in other standard: RAL7032 or RAL9006 其它颜色的标准油漆 RAL7032 或 RAL9006	All
检验报告 Testing certificate		
B02	出厂检验报告 Acceptance test certificate 3.1 according to EN 10204	All

* 电机为 B5 法兰时, 无需指定接线盒位置。

Indication of terminal box position is not necessary when motor is B5 design.

面漆

标准颜色为石头灰RAL7030, 有其它两种颜色可选, 选件号为 Y53。订货时须明确RAL7032或RAL9006。

Paint finish

Standard colour is RAL7030, two other special colours can be offered by option Y53. When ordering, please specify RAL7032 or RAL9006.